



MAGLOK™ DRAGONBOARD®

Fibre Reinforced Magnesium Flooring Board Substrate

CONTENTS

1. Waterproofing solution for tiled showers and bathrooms
2. Standard solution for tiled non-wet areas
3. Levelling solution for vinyl areas
4. Waterproofing preparation solution for outdoor butanol decking areas
5. CEMIX® CEMSEAL WB
6. CEMIX® TILE BOND LATEX
7. CEMIX® RUBBERGUARD
8. CEMIX® RUBBERGUARD TAPES
9. CEMIX® WALLSET WHITE
10. CEMIX® FLOOR TILE ADHESIVE
11. CEMIX® FLEXIBLE COLOURED GROUT
12. CEMIX® GROUT SEALER
13. CEMIX® FLOOR LEVELLER
14. Notes

1. WATERPROOFING SOLUTION FOR TILED SHOWERS AND BATHROOMS

The following materials from CEMIX® CONCRETE PRODUCTS LTD are for use with the MAGLOK™ DRAGONBOARD® - Fibre reinforced magnesium flooring board substrate. They are, where and as prescribed, for use as a water proofing solution for tiled showers and bathrooms over MAGLOK™ DRAGONBOARD®.

WHITE GROUTED WET AREAS

- CEMIX® CEMSEAL WB
- CEMIX® TILE BOND LATEX
- CEMIX® RUBBERGUARD
- CEMIX® RUBBERGUARD TAPES
- CEMIX® WALLSET WHITE
- CEMIX® FLEXIBLE COLOURED GROUT (Recommended colours: White / Vanilla / Ivory / Beige)
- CEMIX® GROUT SEALER

GREY GROUTED WET AREAS

- CEMIX® CEMSEAL
- CEMIX® TILE BOND LATEX
- CEMIX® RUBBERGUARD
- CEMIX® RUBBERGUARD TAPES
- CEMIX® FLOOR TILE ADHESIVE
- CEMIX® FLEXIBLE COLOURED GROUT (Recommended colours: Light Grey / Dark Grey / Black)
- CEMIX® GROUT SEALER

2. STANDARD SOLUTION FOR TILED NON-WET AREAS

The following materials from CEMIX® CONCRETE PRODUCTS LTD are for use with the MAGLOK™ DRAGONBOARD® - Fibre reinforced magnesium flooring board substrate. They are, where and as prescribed, for use as a standard solution for tiled non-wet areas over MAGLOK™ DRAGONBOARD®.

WHITE GROUTED NON-WET AREAS

- CEMIX® CEMSEAL WB
- CEMIX® TILE BOND LATEX
- CEMIX® WALLSET WHITE
- CEMIX® FLEXIBLE COLOURED GROUT (Recommended colours: White / Vanilla / Ivory / Beige)

GREY GROUTED NON-WET AREAS

- CEMIX® CEMSEAL WB
- CEMIX® TILE BOND LATEX
- CEMIX® FLOOR TILE ADHESIVE
- CEMIX® FLEXIBLE COLOURED GROUT (Recommended colours: Light Grey / Dark Grey / Black)

3. LEVELLING SOLUTION FOR VINYL AREAS

The following materials from CEMIX® CONCRETE PRODUCTS LTD are for use with the MAGLOK™ DRAGONBOARD® - Fibre reinforced magnesium flooring board substrate. They are, where and as prescribed, for use as a levelling solution for vinyl areas over MAGLOK™ DRAGONBOARD®.

ALL APPLICATIONS

- CEMIX® CEMSEAL WB
- CEMIX® FLOOR LEVELLER

4. WATERPROOFING PREPARATION SOLUTION FOR OUTDOOR BUTANOL DECKING AREAS

The following materials from CEMIX® CONCRETE PRODUCTS LTD are for use with the MAGLOK™ DRAGONBOARD® - Fibre reinforced magnesium flooring board substrate. They are, where and as prescribed, for use as a waterproofing preparation solution for outdoor butanol decking areas, under MAGLOK™ DRAGONBOARD®.

ALL APPLICATIONS

- CEMIX® CEMSEAL WB

5. CEMIX® CEMSEAL WB

CEMIX® CEMSEAL WB is a penetrating silane-siloxane emulsion which acts as a high quality general purpose water repellent for a variety of surfaces. It is breathable, which assists in preventing condensation and mildew growth. CEMIX® CEMSEAL WB does not produce any discoloration or darkening of the surface.

6. CEMIX® TILE BOND LATEX

CEMIX® TILE BOND LATEX is a modified co-polymer latex specifically formulated to be used as a primer for porous substrates, wallboard, cement sheets, concrete, screed, timber etc. It can also be used as an additive in place of water to fortify, modify and improve grouts, screeds and certain tile adhesives.

7. CEMIX® RUBBERGUARD

CEMIX® RUBBERGUARD is an elastomeric, single component waterproofing membrane. It is based on high performance polymer technology which offers an easy to use one component membrane free of solvents and isocyanates. CEMIX® RUBBERGUARD offers excellent adhesion properties over substrates including concrete, masonry, renders, cement sheeting, wet area sheet surfaces and plaster board surfaces. It is compatible with the CEMIX® range of polymer modified cement-based tile adhesives, screeds and renders.

8. CEMIX® RUBBERGUARD TAPES

The CEMIX® CONCRETE PRODUCTS LTD range of Safeguard self-adhesive tapes assist in ensuring a quality watertight seal, which will accommodate movement in a variety of different waterproofing applications.

- Waterproofing Corner 270 External
- Waterproofing Corner 90 Internal
- Waterproofing Pipe Sleeve 360
- Waterproofing Peel & Seal Tape
- Waterproofing Reinforcing Tape

9. CEMIX® WALLSET WHITE

CEMIX® WALLSET WHITE tile adhesive is a highly flexible, polymer modified, cement-based water-resistant adhesive used for internal and external wall and floor applications including bathrooms, toilets, laundries, kitchens and deck areas. It is suitable over concrete, cement renders, screeds, timber floors with fibrous cement sheeting, plasterboard and CEMIX® approved waterproofing membranes.

10. CEMIX® FLOOR TILE ADHESIVE

CEMIX® FLOOR TILE ADHESIVE is a highly flexible, polymer modified, cement-based water-resistant adhesive used for internal and external wall and floor applications including bathrooms, toilets, laundries, kitchens and deck areas. It is suitable over concrete, cement renders, screeds, timber floors with fibrous cement sheeting, plasterboard and CEMIX® approved waterproofing membranes.

11. CEMIX® FLEXIBLE COLOURED GROUT

CEMIX® FLEXIBLE COLOURED GROUT is a flexible, smooth finish cementitious grout, designed for use with most types of mosaics, ceramic tiles and natural stone. It can be used in internal or external wall and floor grouting applications for joints between 1mm - 8mm.

12. CEMIX® GROUT SEALER

CEMIX® GROUT SEALER is a stain resistant, invisible, water based penetrating clear waterproofing sealer, used for impregnating and sealing of grout. It will resist water, oil and acid-based contaminants.

13. CEMIX® FLOOR LEVELLER

CEMIX® FLOOR LEVELLER is a cement-based levelling compound for application at a thickness between 3mm - 30mm. Under normal conditions access to the floor is available after 1 -3 hours and flooring can be laid after 7 days. CEMIX® FLOOR LEVELLER is to be used where the surface needs to be smooth prior to laying vinyl, typically at joins and screw hole areas. It is used by pouring a slurry, mixed to an acceptable viscosity, in to the joints and the screw holes.

14. NOTES

For full instructions refer to product packaging or contact CEMIX® CONCRETE PRODUCTS LTD on 0800 ASK CEMIX (0800 275 23649).

Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this products packaging, CEMIX® PRODUCTS LTD does not give any warranty express or implied as to suitability for any particular use. For all advice concerning the use of, or suitability of this product for a particular application please contact CEMIX® PRODUCTS LTD. If this product is defective, please contact the merchant the material was purchased from or CEMIX® PRODUCTS LTD who will refund or replace it at no cost in accordance with the requirements of the Consumer Guarantees Act.